

Self-locking Nylon Cable Ties



产品特点 / Product Features

- Material: Nylon 66,94v-2
- Operating temperature: -40C to 85C
- Color: Natural(or white,standard color)UV black and other colors are available as requested.
- Certificate:UL E220676

Part Number			W	Bundle Diameter E(mm)	Min.loop Tensile Strength	
	INCH	MM			LBS	KGS
3*60	2.4	60	1.9	2-11	14	6.5
3*80	3.2	80		2-18		
3*100	4.0	100		2-22		
3*120	4.7	120		2-30		
3*150	6.0	150		2-35		
3*200	8.0	200	2.0	2-50	14	6.5
3*80	3.2	80		2-18		
3*100	4.0	100		2-22		
3*120	4.7	120	2.2	2-30	18	8
3*120	4.7	120		2-30		
3*150	6.0	150		2-35		
3*180	7.1	180		2-42		
3*200	8.0	200	2.2	3-50	18	8
3*80	3.2	80	2.5	2-16	18	8
3*100	4.0	100		2-22		
3*120	4.7	120		2-30		
3*150	6.0	150		2-35		
3*200	8.0	200	2.6	3-50	18	8
3*150	6.0	150		2-35		
3*200	8.0	200		3-50		

Part Number			W	Bundle Diameter E(mm)	Min.loop Tensile Strength	
	INCH	MM			LBS	KGS
3*180	7.1	180	2.8	3-42	27	12
3*200	8.0	200		3-50		
4*250	10	250		3-65		
4*300	12	300		3-80		
4*150	6.0	150	3.0	3-35	33	15
4*250	10	250		3-65		
4*120	4.7	120	3.2	3-30	40	18
4*180	7.1	180		6-42		
4*200	8.0	200		3-50		
4*250	10	250		3-65		
4*300	12	300	3.6	3-80	40	18
4*140	5.5	140		3-33		
4*150	6.0	150		3-35		
5*200	8.0	200		3-50		
5*250	10	250	3.5	3-65	40	18
5*250	10	250		3-65		
5*300	12	300		3-80		
5*300	12	300		3-80		
5*350	14	350	3.6	3-90	40	18
5*370	14.6	370		3-98		
5*400	16	400		3-105		
5*450	17.7	450		3-130		
5*500	19.7	500	4.0	3-150	40	18
5*200	8.0	200		3-50		
5*250	10	250		3-65		
5*300	12	300		3-80		
5*200	8.0	200	4.6	3-50	50	22
5*250	10	250		3-65		
5*300	12	300		3-80		
5*350	14	350		3-90		
5*380	15	380	4.8	3-102	50	22
5*400	16	400		3-105		
5*450	17.7	450		3-130		
5*500	19.7	500		3-150		
5*200	8.0	200	4.8	3-50	50	22
5*250	10	250		3-65		
5*300	12	300		3-80		
5*350	14	350		3-90		
5*370	14.6	370	4.8	3-98	50	22
5*400	16	400		3-105		
5*450	17.7	450		3-130		
5*500	19.7	500		3-150		
8*200	8.0	200	5.2	3-50	65	30
8*250	10	250		3-65		
8*300	12	300		3-80		
8*350	14	350		3-90		
8*400	16	400	5.5	3-105	65	30
8*450	17.7	450		3-130		
8*500	19.7	500		3-150		

Cortisone nylon tie



Cable Ties / Wiring Accessories

/Product Features

- Material: Made of UL approved Nylon 66, fire grade 94v-2.
- Operating Temperature: -40°C~85°C.
- The cortisone nylon tie-in is based on the ordinary nylon tie-in with an added back button so it can be reused.

Product Parameters

Part Number	L		W	Bundle Diameter E(mm)	Min.loop Tensile Strength	
	INCH	MM			LBS	KGS
4×150	6	150	3.6	3-35	40	18
4×200	8	200		3-50		
4×250	10	250		3-65		
4×300	12	300		3-78		
5×150	6	150	4.8	4-35	50	22
5×200	8	200		4-50		
5×250	10	250		4-65		
5×300	12	300		4-78		
8×100	4	100	7.2	5-22	110	48
8×150	6	150		5-35		
8×200	8	200		5-50		
8×250	10	250		5-65		
8×300	12	300		5-78		
8×350	14	350		5-92		
8×400	16	400		5-106		
8×450	18	450		5-120		
8×500	20	500		5-135		
8×550	22	550		5-152		
8×600	24	600	8.8	5-168	160	70
8×700	28	700		5-197		
10×800	32	800		8-220		
10×1000	40	1000		8-285		
10×1200	48	1200		8-350		
10×1500	60	1500		8-445		

Car Bolt harness belt

/Product Features

- Material: Made of UL approved Nylon 66, fire grade 94v-2.
- Operating Temperature: -40°C TO 85°C.
- is widely used for wiring harness fixing in automobile and ship industries. It has the characteristics of acid resistance, corrosion resistance, insulation and UV resistance.



Part number	Size			Aperture	(mm) Applicable plate thickness	Max, bundle diamm(inch)
	L	W	H			
3*100	100	2.5	1	5mm	1-3mm	2-22mm
5*150	150	4.8	1.2	6-7mm	0.8-5mm	5-28mm
5*160	160	4.8	1.3	6-7mm	0.6-4.2mm	5-30mm
5*165	165	4.8	1.2	7mm	0.6-4.5mm	5-33mm
6*210	210	5.4	1.3	6-7mm	0.6-6mm	6-47mm
5*220	220	4.8	1.2	7mm	1-5mm	5-50mm



Part number	Size			Aperture	(mm) Applicable plate thickness	Max, bundle diamm(inch)
	L	W	H			
4*150	150	3.6	1.1	4.5mm	0.6-2.0mm	3-38mm
4*200	200	3.6	1.1	4.5mm	0.6-2.0mm	3-53mm
5*160	160	4.7	1.25	6-7mm	0.6-3mm	4-35mm
5*200	200	4.8	1.3	6mm	0.6-3mm	4-53mm
6*130	130	5.5	1.3	6-7mm	0.6-2.0mm	5-32mm
8*150	150	7.6	1.5	5.5-6mm	0.6-2.0mm	5-38mm
7*170	170	6.4	1.4	7mm	0.6-2.0mm	5-35mm
9*170	170	8.6	1.6	7*12mm	0.6-2.0mm	8-35mm
5*170	170	5	1.36	M5-M6	M6螺栓	5-36mm
5*160	160	4.7	1.35	M5-M6	M3螺栓	5-35mm



Car base plate fixing strap

Part number	Size			Aperture	Max, bundle diamm(inch)
	L	W	H		
5*250	250	4.8	1.35	5mm	6-61mm
8*280	280	7.6	1.4	8mm	8-70mm
8*370	370	7.6	1.7	8mm	8-98mm

/ Product Features

- / ProductParameters

Part number	Approx. lengthmm(inch)		Approx. widthmm(inch)	Binding range	拉力 Min loop Tensile Strength	
	INCH	MM			LBS	KGS
3×100	4	100	2.5	2-22	27	12
4×150	6	150	3.6	3-35	50	22
4×200	8	200		3-50		
5×250	10	250	4.8	3-65	68	30
5×300	12	300		3-80		
8×145	5.8	145	7.2	4-34	135	60
8×175	7	175		4-40		
8×200	8	200		4-50		
8×400	16	400		4-102		
10×300	12	300	8.8	6-80	225	100
10×350	14	350		6-92		
10×400	16	400		6-108		
10×450	18	450		6-130		
10×550	22	550		6-158		
10×600	24	600		6-172		

Part number	Approx. lengthmm (inch)		Approx. widthmm (inch)	Binding range	Min loop Tensile Strength		Pcs/bag
	INCH	MM			LBS	KGS	
1×100	4	100	2.5mm	2-22	18	8	500
4×150	6	150	2.8mm	2-35	33	16	250
4×200	8	200	2.8mm	3-50	33	16	250

Part number	Approx. lengthmm (inch)		Approx. widthmm (inch)	Binding range	Min loop Tensile Strength		Pcs/bag
	INCH	MM			LBS	KGS	
12×700	28	700	12mm		214	95	10
13×700	28	700	13mm		214	95	10
13×900	36	900	13mm		232	103	10

Part number	Approx. lengthmm(inch)		Approx. widthmm (inch)	Binding range	Min loop Tensile Strength		Pcs/bag
	INCH	MM			LBS	KGS	
5×200	8	200	4.8mm	8-50	49.5	22	100
5×225	9	225	4.8mm	8-58	49.5	22	100
5×250	10	250	4.8mm	8-65	49.5	22	100
5×300	12	300	4.8mm	8-80	49.5	22	100
5×330	13.2	330	4.8mm	8-88	49.5	22	100
5×370	14.8	370	4.8mm	8-95	49.5	22	100
5×380	15.2	380	4.8mm	8-97	49.5	22	100
5×400	16	400	4.8mm	8-101	49.5	22	100

Part number	Approx. lengthmm(inch)		Approx. widthmm (inch)	Binding range	M in loop Tensile Strength		Pcs/bag
	INCH	MM			LBS	KGS	
3×100	4	100	2.5mm	2-22	18	8	100
4×150	6	150	3.6mm	2-35	36	16	100
4×200	8	200	3.6mm	3-50	40.5	18	100
5×200	8	200	4.8mm	5-50	49.5	22	100
5×250	10	250	4.8mm	5-65	49.5	22	100

Naked Stainless Steel Cable Ties-Ball Self-Lock



Product Features

- Characteristic : They have a unique ball locking mechanism that allow easily and quickly installed and not undone;
- High tensile strength : Non-flammability;
- Temperature : Working temperature - 60°C~550°C ;
- High resistance to a cetica cid, alkali acid, sulphuric acid, corrode etc ;
- All length are available, stainless steel type:304,316.

/ Product Parameters

Part number	Approx. lengthmm (inch)	Approx. widthmm (inch)	Thickness	Max, bundle diammm (inch)	Min. loop tensile strenth N (lbs)	Pcs/bag
4.6×150	150(5.9)	4.6(0.181)	0.4	37(1.46)	600(135)	100
4.6×200	200(7.87)		0.4	50(1.97)		100
4.6×250	250(9.84)		0.4	63(2.48)		100
4.6×300	300(11.8)		0.4	76(2.99)		100
4.6×350	350(13.78)		0.4	89(3.5)		100
4.6×400	400(15.75)		0.4	102(4.02)		100
4.6×450	450(17.72)		0.4	115(4.53)		100
4.6×500	500(19.69)		0.4	128(5.04)		100
4.6×550	550(21.65)		0.4	141(5.55)		100
4.6×600	600(23.62)		0.4	154(6.06)		100
7.9×150	150(5.9)	7.9(0.311)	0.4	37(1.46)	800(180)	100
7.9×200	200(7.87)		0.4	50(1.97)		100
7.9×250	250(9.84)		0.4	63(2.48)		100
7.9×300	300(11.8)		0.4	76(2.99)		100
7.9×350	350(13.78)		0.4	89(3.5)		100
7.9×400	400(15.75)		0.4	102(4.02)		100
7.9×450	450(17.72)		0.4	115(4.53)		100
7.9×500	500(19.69)		0.4	128(5.04)		100
7.9×550	550(21.65)		0.4	141(5.55)		100
7.9×600	600(23.62)		0.4	154(6.06)		100
7.9×650	650(25.59)		0.4	167(6.57)		100
7.9×700	700(27.56)		0.4	180(7.09)		100
7.9×750	750(29.53)		0.4	191(7.52)		100
7.9×800	800(31.5)		0.4	193(7.59)		100

Stainless Steel Epoxy Coated Cable Ties-Ball Self-Lock



Product Features

- Characteristic: They have a unique ball locking with plastic jetting mechanism that allow easily and quickly installed and not undone;
- High tensile strength: Non-flammability;
- Temperature: Working temperature - 40C~85;
- High resistance to a cetica cid, alkali acid, sulphuric acid, corrode etc;
- All length are available, stainless steel type:304316.

/ Product Parameters

Part number	Approx. lengthmm (inch)	Approx. widthmm (inch)	Thickness	Max, bundle diammm (inch)	Min. loop tensile strenth N (lbs)	Pcs/bag
10×150	150(5.9)	10(0.472)	0.25	37(1.46)	1200(270)	100
10×200	200(7.87)		0.25	50(1.97)		100
10×250	250(9.84)		0.25	63(2.48)		100
10×300	300(11.8)		0.25	76(2.99)		100
10×350	350(13.78)		0.25	89(3.5)		100
10×400	400(15.75)		0.25	102(4.02)		100
10×450	450(17.72)		0.25	115(4.53)		100
10×500	500(19.69)		0.25	128(5.04)		100
10×550	550(21.65)		0.25	141(5.55)		100
10×600	600(23.62)		0.25	154(6.06)		100
10×650	650(25.59)	12(0.59)	0.25	167(6.57)	1500(337)	100
10×700	700(27.56)		0.25	180(7.09)		100
12×200	200(7.87)		0.25	50(1.97)		100
12×250	250(9.84)		0.25	63(2.48)		100
12×300	300(11.8)		0.25	76(2.99)		100
12×350	350(13.78)		0.25	89(3.5)		100
12×400	400(15.75)		0.25	102(4.02)		100
12×450	450(17.72)		0.25	115(4.53)		100
12×500	500(19.69)		0.25	128(5.04)		100
12×550	550(21.65)		0.25	141(5.55)		100
12×600	600(23.62)		0.25	154(6.06)		100
12×650	650(25.59)		0.25	167(6.57)		100
12×700	700(27.56)		0.25	180(7.09)		100
12×750	750(29.53)		0.25	191(7.52)		100
12×800	800(31.5)		0.25	193(7.59)		100
12×1000	1000(39.37)		0.25	206(8.11)		100